

Ezee-Glider™ 2000 Technical Data



Spiral blade 22-25 degree, right hand

Spiral blade Size (in)	OD (in)	ID (in)	Length (in)	Weight (kg)	Flowby (sq in)	Blades (No)	Avg. Field Friction Factors
9-7/8 x 12-1/4	12.0	10.00	10	4.2	29.45	5	+/- 0.10
9-5/8 x 12-1/4	12.0	9.750	10	4.3	32.03	5	+/- 0.10
7.0 x 8-1/2	8.25	7.100	10	2.3	11.89	5	+/- 0.10
5-1/2 x 8-1/2	8.25	5.600	10	2.3	25.68	4	+/- 0.10
5.0 x 8-1/2	8.25	5.125	10	2.3	30.25	4	+/- 0.10
5.0 x 6-1/2	6.25	5.125	10	1.2	8.57	4	+/- 0.10
4-1/2 x 8-1/2	8.25	4.600	10	2.2	33.86	4	+/- 0.10
4-1/2 x 6.0	5.75	4.600	8	1.1	8.33	4	+/- 0.10
3-1/2 x 6.0	5.75	3.625	8	0.8	13.97	4	+/- 0.10



Straight blade 5 degree passive angle

5 Deg blade Size (in)	OD (in)	ID (in)	Length (in)	Weight (kg)	Flowby (sq in)	Blades (No)
6-5/8 x 8-1/2	8.25	6.750	10	2.3	17.25	4
5-1/2 x 8-1/2	8.25	5.600	10	2.3	26.23	4
4.0 x 6-1/2	6.25	4.600	8	1.1	15.54	4
2-7/8 x 4-1/2	4.375	2.950	8	0.7	5.74	4

Ezee-Gliders™ come complete with integral metal swage rings inset into each end. Ezee-Gliders™ are available in BOS 21 standard grade engineering polymer and BOS 22 self lubricating polymer for low friction WBM applications.